

ENBN RNP -A - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	IXILO	-	-	-5.0	-	-	-	A3800+	-	-	-	1.0
20	TF	BN404	-	-	-5.0	5.0	-	-	A3000+	-	-	-	1.0
10	IF	XODBA	-	-	-5.0	-	-	-	A4900+	-	-	-	1.0
20	TF	BN404	-	-	-5.0	5.0	-	-	A3000+	-	-	-	1.0
10	IF	ULTUL	-	-	-5.0	-	-	-	A4400+	-	-	-	1.0
20	TF	BN404	-	-	-5.0	5.0	-	-	A3000+	-	-	-	1.0
30	TF	BN408	-	-	-5.0	3.8	-	-	A3000+	-	-	-	1.0
40	TF	BN406	Y	-	-5.0	8.0	-	-	-	-	-3.0/-	-	0.3
50	TF	MEDEK	-	-	-5.0	15.2	-	-	-	-	-	-	1.0
60	HM	MEDEK	-	034 (038.9)	-5.0	1 MIN	-	L	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.