

## ENAL RNP Z RWY 06 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	LAPEV	-	-	-2.0	-	-	-	A5000+	-	-	-	1.0
020	TF	UVEVA	-	-	-2.0	7.0	-	-	A3000+	K230-	-	-	1.0
010	IF	ASKEX	-	-	-2.0	-	-	-	A3000+	K230-	-	-	1.0
020	TF	UVEVA	-	-	-2.0	5.0	-	-	A3000+	K230-	-	-	1.0
010	IF	UVEVA	-	-	-2.0	-	-	-	A3000+	K230-	-	-	1.0
020	TF	ATBOL	-	-	-2.0	4.4	-	-	A3000+	-	-	-	1.0
030	TF	AL799	Y	-	-2.0	6.6	-	-	-	-	-3.4/50	-	0.3
040	TF	AL821	Y	-	-2.0	7.9	-	-	-	K185-	-	-	1.0
050	DF	TOMNO	-	-	-2.0	-	-	L	-	K185-	-	-	1.0
060	HM	TOMNO	-	328 (329.5)	-2.0	-	-	R	A5000	K220-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: ATBOL holding not included in standard APCH transitions.