

ENAS RNP RWY 12 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	AS404	-	-	-8.0	-	-	-	A5800+	-	-	-	1.0
020	TF	AS403	-	-	-8.0	6.5	-	-	A3000+	-	-	-	1.0
010	IF	AS405	-	-	-8.0	-	-	-	A3600+	-	-	-	1.0
020	TF	AS403	-	-	-8.0	4.0	-	-	A3000+	-	-	-	1.0
010	IF	AS403	-	-	-8.0	-	-	-	A3000+	-	-	-	1.0
020	TF	AS402	-	-	-8.0	4.0	-	-	A1720+	-	-	-	1.0
030	TF	AS401	Y	-	-8.0	3.0	-	-	-	-	-3.0/50	-	0.3
040	DF	AS405	-	-	-8.0	-	-	L	-	K130-	-	-	1.0
050	HM	AS405	-	051 (059.0)	-8.0	-	-	L	A3000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.