

ENAS RNP RWY 30 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	AS604	-	-	-8.0	-	-	-	A5200+	-	-	-	1.0
020	TF	AS603	-	-	-8.0	5.0	-	-	A5200+	-	-	-	1.0
010	IF	AS605	-	-	-8.0	-	-	-	A5800+	-	-	-	1.0
020	TF	AS603	-	-	-8.0	5.0	-	-	A5200+	-	-	-	1.0
010	IF	AS603	-	-	-8.0	-	-	-	A5200+	-	-	-	1.0
020	TF	AS602	-	-	-8.0	4.0	-	-	A3650+	-	-	-	1.0
030	TF	AS601	Y	-	-8.0	8.0	-	-	-	-	-3.7/50	-	0.3
040	DF	AS402	-	-	-8.0	-	-	-	-	K130-	-	-	1.0
050	TF	AS405	-	-	-8.0	5.7	-	-	-	-	-	-	1.0
060	HM	AS405	-	051 (059.0)	-8.0	-	-	L	A3000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: AS603 holding not included in standard APCH transitions.