

ENVA RNP W RWY 27 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAV AID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	NYDAR	-	-	-4.0		-	-	A4500+	-	-	-	1.0
20	TF	VA525	-	-	-4.0	2.3	-	-	A4100+	-	-	-	1.0
30	TF	VA526	-	-	-4.0	1.3	-	-	-	-	-3.4	-	0.3
40	RF	VA534	-	-	-4.0	5.6	-	L	-	K160-	-3.4	VA006 2.300	0.3
50	TF	RW27	-	-	-4.0	4.0	-	-	-	-	-3.4/50	-	0.3
60	TF	VA554	-	-	-4.0	20.0	-	-	-	-	-	-	1.0
70	HM	VA554	-	019 (023.0)	-4.0	1 MIN	-	R	A4000	K230-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: The use of SBAS/GNSS geometric altitude as a source of altitude for approaches to LNAV/VNAV minima is permitted only for aircraft specifically certified for this type of operation. See “EASA CS ACNS.C.PBN.560” for additional information.

RF arc centre coordinates:

RF arc centre identifier	Latitude	Longitude
VA006	63°25'08.295"N	011°05'23.495"E