

ENML RNP RWY 25 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	UTILU	-	-	-2.0	-	-	-	A5000+	K230-	-	-	1.0
020	TF	ABDEM	-	-	-2.0	5.0	-	-	A5000+	K220-	-	-	1.0
010	IF	ERPER	-	-	-2.0	-	-	-	A5000+	K220-	-	-	1.0
020	TF	ABDEM	-	-	-2.0	5.1	-	-	A5000+	K220-	-	-	1.0
030	TF	ML630	-	-	-2.0	4.0	-	-	A4000+	-	-	-	1.0
040	TF	ML631	Y	-	-2.0	10.6	-	-	-	-	-3.5/50	-	0.3
050	FA	ML631	-	244 (246.0)	-2.0	-	-	-	A2600	-	-	-	1.0
060	DF	ERMEG	-	-	-2.0	-	-	R	A4000	-	-	-	1.0
070	HM	ERMEG	-	333 (335.0)	-2.0	1 MIN	-	R	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: The use of SBAS/GNSS geometric altitude as a source of altitude for approaches to LNAV/VNAV minima is permitted only for aircraft specifically certified for this type of operation. See “EASA CS ACNS.C.PBN.560” for additional information.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 200 FT shall not be used due to approach operation Type B limitations.

Note: ABDEM holding not included in standard APCH transitions.

FAS DB

Operation type	0	LTP/FTP ellipsoidal height	47.4
SBAS provider	1	FPAP latitude	624443.0325N
Airport identifier	ENML	FPAP longitude	0071451.4510E
Runway	RW25	Threshold crossing height	50
Approach performance designator	0	TCH units	FT
Route indicator	-	Glide path angle	3.5
Reference path data selector	0	Course width at threshold	105
Reference path identifier	E25A	Length offset	0
LTP/FTP latitude	624458.5085N	Horizontal alert limit (HAL)	40
LTP/FTP longitude	0071706.8120E	Vertical alert limit (VAL)	35
		PRECISION APPROACH PATH CRC REMAINDER	F16D0BEA