

ENSB RNP-A - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	NAXEN	-	-	-10.0	-	-	-	A5000+	-	-	-	1.0
020	TF	SB703	-	-	-10.0	7.5	-	-	A4700+	-	-	-	1.0
010	IF	RARAG	-	-	-10.0	-	-	-	A5100+	-	-	-	1.0
020	TF	SB703	-	-	-10.0	4.3	-	-	A4700+	-	-	-	1.0
010	IF	SB703	-	-	-10.0	-	-	-	A4700+	-	-	-	1.0
020	TF	SB704	-	-	-10.0	5.0	-	-	A4700+	-	-	-	1.0
030	TF	SB709	Y	-	-10.0	11.2	-	-	-	-	-4.4/-	-	0.3
040	TF	SB705	-	-	-10.0	3.7	-	-	-	-	-	-	1.0
050	TF	SB706	-	-	-10.0	6.5	-	-	-	-	-	-	1.0
060	TF	SB707	-	-	-10.0	4.8	-	-	-	-	-	-	1.0
070	TF	SB708	-	-	-10.0	6.7	-	-	-	-	-	-	1.0
080	TF	NAXEN	-	-	-10.0	28.2	-	-	-	-	-	-	1.0
090	HM	NAXEN	-	222 (232.2)	-10.0	1 MIN	-	L	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.