

ENOV RNP-A - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	NIKUD	-	-	-2.0	-	-	-	A7000+	-	-	-	1.0
020	TF	OV411	-	-	-2.0	5.0	-	-	A6900+	-	-	-	1.0
010	IF	KOKIS	-	-	-2.0	-	-	-	A7000+	-	-	-	1.0
020	TF	OV411	-	-	-2.0	5.0	-	-	A6900+	-	-	-	1.0
010	IF	OSLOS	-	-	-2.0	-	-	-	A9000+	-	-	-	1.0
020	TF	OV411	-	-	-2.0	4.8	-	-	A6900+	-	-	-	1.0
030	TF	OV412	-	-	-2.0	4.0	-	-	A6000+	-	-	-	1.0
040	TF	OV413	Y	-	-2.0	8.7	-	-	-	-	-4.0	-	0.3
050	TF	OV414	-	-	-2.0	5.0	-	-	-	K130-	-	-	1.0
060	TF	BVK	-	-	-2.0	6.8	-	-	-	-	-	-	1.0
070	HM	BVK	-	126 (128.0)	-2.0	1 MIN	-	L	A4600	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.