

ENSS RNP RWY 15 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	NILIP	-	-	-17.0	-	-	-	A4000+	-	-	-	1.0
020	TF	AGLOB	-	-	-17.0	5.0	-	-	A2500+	-	-	-	1.0
010	IF	AGLOB	-	-	-17.0	-	-	-	A2500+	-	-	-	1.0
020	TF	SS806	-	-	-17.0	4.0	-	-	A2000+	-	-	-	1.0
030	TF	RW15	Y	-	-17.0	4.6	-	-	-	-	-3.9/50	-	0.3
040	TF	SS810	Y	-	-17.0	9.0	-	-	-	-	-	-	1.0
050	DF	NILIP	-	-	-17.0	-	-	L	-	-	-	-	1.0
060	HM	NILIP	-	056 (072.9)	-17.0	1 MIN	-	L	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: The use of SBAS/GNSS geometric altitude as a source of altitude for approaches to LNAV/VNAV minima is permitted only for aircraft specifically certified for this type of operation. See “EASA CS ACNS.C.PBN.560” for additional information.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.

FAS DB

Operation type	0	LTP/FTP ellipsoidal height	31.3
SBAS provider	1	FPAP latitude	702041.7875N
Airport identifier	ENSS	FPAP longitude	0310315.1765E
Runway	RW15	Threshold crossing height	50
Approach performance designator	0	TCH units	FT
Route indicator	-	Glide path angle	3.9
Reference path data selector	0	Course width at threshold	105
Reference path identifier	E15A	Length offset	616
LTP/FTP latitude	702134.1700N	Horizontal alert limit (HAL)	40
LTP/FTP longitude	0310228.4285E	Vertical alert limit (VAL)	50
PRECISION APPROACH PATH CRC REMAINDER			1036D252