

ENSS RNP Y RWY 33 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	GAMKI	-	-	-17.0	-	-	-	A4000+	-	-	-	1.0
020	TF	SS608	-	-	-17.0	5.0	-	-	A4000+	-	-	-	1.0
030	TF	SS607	-	-	-17.0	5.4	-	-	A2000+	-	-	-	1.0
040	TF	SS609	Y	-	-17.0	3.0	-	-	-	-	-3.9/50	-	0.3
050	TF	SS611	Y	-	-17.0	10.1	-	-	-	-	-	-	1.0
060	DF	GAMKI	-	-	-17.0	-	-	R	-	-	-	-	1.0
070	HM	GAMKI	-	036 (053.0)	-17.0	1 MIN	-	L	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.