

ENSS RNP Z RWY 33 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	GAMKI	-	-	-17.0	-	-	-	A4000+	-	-	-	1.0
020	TF	SS608	-	-	-17.0	5.0	-	-	A4000+	-	-	-	1.0
030	TF	SS607	-	-	-17.0	5.4	-	-	A2000+	-	-	-	1.0
040	TF	RW33	Y	-	-17.0	4.7	-	-	-	-	-3.9/50	-	0.3
050	TF	SS611	Y	-	-17.0	8.5	-	-	-	-	-	-	1.0
060	DF	GAMKI	-	-	-17.0	-	-	R	-	-	-	-	1.0
070	HM	GAMKI	-	036 (053.0)	-17.0	1 MIN	-	L	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: The use of SBAS/GNSS geometric altitude as a source of altitude for approaches to LNAV/VNAV minima is permitted only for aircraft specifically certified for this type of operation. See “EASA CS ACNS.C.PBN.560” for additional information.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.

FAS DB

Operation type	0	LTP/FTP ellipsoidal height	025.8
SBAS provider	1	FPAP latitude	702154.8715N
Airport identifier	ENSS	FPAP longitude	0310209.9345E
Runway	RW33	Threshold crossing height	50
Approach performance designator	0	TCH units	FT
Route indicator	Z	Glide path angle	3.9
Reference path data selector	0	Course width at threshold	105
Reference path identifier	E33A	Length offset	616
LTP/FTP latitude	702102.4895N	Horizontal alert limit (HAL)	40
LTP/FTP longitude	0310256.7060E	Vertical alert limit (VAL)	50
		PRECISION APPROACH PATH CRC REMAINDER	E120553E