

ENBS RNP RWY 03 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	ERNIX	-	-	-16.0	-	-	-	A4000+	-	-	-	1.0
020	TF	MIKDU	-	-	-16.0	5.0	-	-	A4000+	-	-	-	1.0
010	IF	BITBO	-	-	-16.0	-	-	-	A4000+	-	-	-	1.0
020	TF	MIKDU	-	-	-16.0	5.0	-	-	A4000+	-	-	-	1.0
010	IF	MIKDU	-	-	-16.0	-	-	-	A4000+	-	-	-	1.0
020	TF	BS410	-	-	-16.0	4.0	-	-	A4000+	-	-	-	1.0
030	TF	RW03	Y	-	-16.0	8.4	-	-	-	-	-3.9/50	-	0.3
040	TF	BS420	Y	-	-16.0	7.8	-	-	-	-	-	-	1.0
050	DF	MIKDU	-	-	-16.0	-	-	R	-	-	-	-	1.0
060	HM	MIKDU	-	028 (043.6)	-16.0	1 MIN	-	R	A4000	-	-	-	1.0

Note: MIKDU holding not included in standard APCH transitions.

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: The use of SBAS/GNSS geometric altitude as a source of altitude for approaches to LNAV/VNAV minima is permitted only for aircraft specifically certified for this type of operation. See “EASA CS ACNS.C.PBN.560” for additional information.

FAS DB

Operation type	0	LTP/FTP ellipsoidal height	166.6
SBAS provider	1	FPAP latitude	703628.6365N
Airport identifier	ENBS	FPAP longitude	0294254.2650E
Runway	RW03	Threshold crossing height	50
Approach performance designator	0	TCH units	FT
Route indicator	-	Glide path angle	3.9
Reference path data selector	0	Course width at threshold	105
Reference path identifier	E03A	Length offset	696
LTP/FTP latitude	703549.3145N	Horizontal alert limit (HAL)	40
LTP/FTP longitude	0294059.8920E	Vertical alert limit (VAL)	50
	PRECISION APPROACH PATH CRC REMAINDER		80DF4EDC