ENGM RNP E RWY 01L (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	SUBZO	-	-	-4.0	-	-	-	A5000+	K220-	-	-	1.0
20	TF	GM625	-	-	-4.0	5.1	-	-	A3700+	K200-	-	-	1.0
30	RF	GM626	-	-	-4.0	1.8	-	R	A3200+	-	-	GM011 3.100	0.7
40	TF	GM627	-	-	-4.0	1.8	-	-	A2700+	-	-	-	0.7
50	RF	GM553	-	-	-4.0	2.9	-	R	A1800+	-	-	GM013 3.000	0.7
60	TF	RW01L	-	-	-4.0	3.4	-	-	-	-	-3.0/50	-	0.3
70	TF	GM918	Y	-	-4.0	21.1	-	-	-	-	-	-	1.0
80	DF	GRM	-	-	-4.0	-	-	L	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: The use of SBAS/GNSS geometric altitude as a source of altitude for approaches to LNAV/VNAV minima is permitted only for aircraft specifically certified for this type of operation. See “EASA CS ACNS.C.PBN.560” for additional information.

RF arc centre coordinates:

RF arc centre identifier	Latitude	Longitude
GM011	600539.55N	0111049.77E
GM013	600700.81N	0110818.75E