

ENST RNP Z RWY 02 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	AFAKE	-	-	-5.0	-	-	-	A4600+	-	-	-	1.0
20	TF	ST419	-	-	-5.0	5.0	-	-	A3000+	-	-	-	1.0
10	IF	SEGKA	-	-	-5.0	-	-	-	A5000+	-	-	-	1.0
20	TF	ST419	-	-	-5.0	5.5	-	-	A3000+	-	-	-	1.0
30	TF	ST418	-	-	-5.0	4.4	-	-	A2000+	-	-	-	1.0
40	TF	ST417	Y	-	-5.0	6.0	-	-	-	-	-3.0/50	-	0.3
50	CA	-	-	031 (035.8)	-5.0	-	-	-	A2700	-	-	-	1.0
60	DF	UGMAL	-	-	-5.0	-	-	L		-	-	-	1.0
70	HM	UGMAL	-	265 (269.9)	-5.0	1 MIN	-	R	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: The use of SBAS/GNSS geometric altitude as a source of altitude for approaches to LNAV/VNAV minima is permitted only for aircraft specifically certified for this type of operation. See “EASA CS ACNS.C.PBN.560” for additional information

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.