

ENNO RNP RWY 12 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	USSAF	-	-	-3.0	-	-	-	A7300+	-	-	-	1.0
020	TF	NO422	-	-	-3.0	5.7	-	-	A4800+	K220-	-	-	1.0
010	IF	TILTE	-	-	-3.0	-	-	-	A5700+	-	-	-	1.0
020	TF	NO422	-	-	-3.0	5.0	-	-	A4800+	K220-	-	-	1.0
010	IF	FALLE	-	-	-3.0	-	-	-	A6000+	-	-	-	1.0
020	TF	NO423	-	-	-3.0	3.0	-	-	A5700+	-	-	-	1.0
030	TF	NO422	-	-	-3.0	3.6	-	-	A4800+	K220-	-	-	1.0
040	TF	NO421	-	-	-3.0	4.3	-	-	A4100+	-	-	-	1.0
050	TF	NO420	Y	-	-3.0	7.9	-	-	-	-	-3.9/50	-	0.3
060	FA	NO420	-	-	-3.0	-	-	-	A2900	-	-	-	1.0
070	DF	FOGGO	-	-	-3.0	-	-	R	A4000	-	-	-	1.0
080	HM	FOGGO	-	318 (321.3)	-3.0	1 MIN	-	R	A4000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.