

ENNO RNP RWY 30 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	MATZE	-	-	-3.0	-	-	-	A4300+	-	-	-	1.0
020	TF	FOGGO	-	-	-3.0	5.0	-	-	A4000+	K220-	-	-	1.0
010	IF	UMUME	-	-	-3.0	-	-	-	A4800+	-	-	-	1.0
020	TF	FOGGO	-	-	-3.0	5.0	-	-	A4000+	K220-	-	-	1.0
010	IF	FOGGO	-	-	-3.0	-	-	-	A4000+	K220-	-	-	1.0
020	TF	NO502	-	-	-3.0	4.3	-	-	A3500+	-	-	-	1.0
030	TF	NO501	Y	-	-3.0	7.2	-	-	-	-	-3.7/50	-	0.3
040	FA	NO501	-	-	-3.0	-	-	-	A3700	-	-	-	1.0
050	DF	FALLE	-	-	-3.0	-	-	L	A6000	-	-	-	1.0
060	HM	FALLE	-	022 (024.8)	-3.0	1 MIN	-	R	A6000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.