

ENZV RNP Y RWY 10 (CAT H) - RECOMMENDED CODING

-	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	WESTY	-	-	-2.0	-	-	-	A1000+	-	-	-	1.0
20	TF	IVLIL	-	-	-2.0	7.3	-	-	A1000+	-	-	-	1.0
10	IF	AMKIK	-	-	-2.0	-	-	-	A1000+	-	-	-	1.0
20	TF	IVLIL	-	-	-2.0	3.0	-	-	A1000+	-	-	-	1.0
30	TF	ZV407	-	-	-2.0	3.5	-	-	A1000+	-	-	-	1.0
40	TF	ZV408	Y	-	-2.0	1.7	-	-	-	-	-3.0 / 35	-	0.3
50	DF	ZV409	Y	-	-2.0	-	-	R	A1000	-	-	-	1.0
60	DF	AMKIK	-	-	-2.0	-	-	R	-	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.