

ENVR RNP 197 - RECOMMENDED CODING

| SN | PD | WI    | Fly-over | °M (°T)     | MAG VAR | DIST (NM) | REC NAVAID | TD | ALT (FT) | Speed (KT) | VPA (°)/ TCH (FT) | ARC CENTRE RADIUS (NM) | RNP (NM) |
|----|----|-------|----------|-------------|---------|-----------|------------|----|----------|------------|-------------------|------------------------|----------|
| 10 | IF | ROSAP | -        | -           | -6.0    | -         | -          | -  | A1500+   | -          | -                 | -                      | 1.0      |
| 20 | TF | VR630 | -        | -           | -6.0    | 3.0       | -          | -  | A1500+   | -          | -                 | -                      | 1.0      |
| 30 | TF | VR640 | -        | -           | -6.0    | 3.0       | -          | L  | A1500+   | -          | -                 | -                      | 1.0      |
| 40 | TF | VR650 | -        | -           | -6.0    | 2.2       | -          | -  | -        | -          | -3.7/-            | -                      | 0.3      |
| 50 | TF | VR660 | Y        | -           | -6.0    | 0.75      | -          | -  | -        | -          | -                 | -                      | 0.3      |
| 60 | TF | VR670 | -        | -           | -6.0    | 3.7       | -          | -  | -        | -          | -                 | -                      | 1.0      |
| 70 | TF | VR770 | -        | -           | -6.0    | 6.6       | -          | L  | -        | -          | -                 | -                      | 1.0      |
| 80 | TF | VEXIM | -        | -           | -6.0    | 3.0       | -          | L  | A1200    | -          | -                 | -                      | 1.0      |
| 90 | HM | VEXIM | -        | 264 (270.0) | -6.0    | 1 MIN     | -          | R  | A1200    | K110-      | -                 | -                      | 1.0      |

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.