

ENBN RNP X RWY 03 (LPV only) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	ABRAK	-	-	-5.0	-	-	-	A3700+	-	-	-	1.0
20	TF	BN420	-	-	-5.0	5.6	-	-	A2500+	-	-	-	1.0
10	IF	GITAP	-	-	-5.0	-	-	-	A3700+	-	-	-	1.0
20	TF	BN420	-	-	-5.0	4.5	-	-	A2500+	-	-	-	1.0
10	IF	MEDEK	-	-	-5.0	-	-	-	A4600+	-	-	-	1.0
20	TF	BN420	-	-	-5.0	4.4	-	-	A2500+	-	-	-	1.0
30	TF	BN421	-	-	-5.0	3.5	-	-	A1900+	-	-	-	1.0
40	TF	FTP	Y	-	-5.0	5.8	-	-	-	-	-3.0/50	-	0.3
50	DF	BN422	Y	-	-5.0	1.5	-	-	-	-	-	-	1.0
60	CF	PEPIB	-	347 (351.8)	-5.0	-	BNN	L	-	-	-	-	1.0
70	FA	-	-	347 (351.8)	-5.0	-	BNN	-	A2600	-	-	-	1.0
80	DF	PEPIB	-	-	-5.0	-	-	L	-	-	-	-	1.0
90	HM	PEPIB	-	167 (171.8)	-5.0	1 MIN	-	R	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.

FAS DB

Operation type	0	LTP/FTP ellipsoidal height	41.1
SBAS provider	1	FPAP latitude	652803.3360N
Airport identifier	ENBN	FPAP longitude	0121332.1760E
Runway	RW03	Threshold crossing height	50
Approach performance designator	0	TCH units	FT
Route indicator	X	Glide path angle	3.0
Reference path data selector	0	Course width at threshold	105
Reference path identifier	E03A	Length offset	0
LTP/FTP latitude	652718.5690N	Horizontal alert limit (HAL)	40
LTP/FTP longitude	0121216.4670E	Vertical alert limit (VAL)	50
	PRECISION APPROACH PATH CRC REMAINDER		D40EA146