

ENAN RNP RWY 32 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	RUTOD	-	-	-8.0	-	-	-	A3600+	-	-	-	1.0
20	TF	IPLUR	-	-	-8.0	5.0	-	-	A2500+	-	-	-	1.0
10	IF	GEVPI	-	-	-8.0	-	-	-	A4300+	-	-	-	1.0
20	TF	IPLUR	-	-	-8.0	5.0	-	-	A2500+	-	-	-	1.0
10	IF	IVGAM	-	-	-8.0	-	-	-	A4400+	-	-	-	1.0
20	TF	IPLUR	-	-	-8.0	5.0	-	-	A2500+	-	-	-	1.0
30	TF	ABSOV	-	-	-8.0	5.4	-	-	A1500+	-	-	-	1.0
40	TF	RW32	Y	-	-8.0	4.5	-	-	-	-	-3.0/50	-	0.3
50	TF	ROBUM	-	-	-8.0	10.1	-	-	-	-	-	-	1.0
60	HM	ROBUM	Y	142 (150.0)	-8.0	1 MIN	-	L	A2000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: The use of SBAS/GNSS geometric altitude as a source of altitude for approaches to LNAV/VNAV minima is permitted only for aircraft specifically certified for this type of operation. See “EASA CS ACNS.C.PBN.560” for additional information.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.

FAS DB

Operation type	0	LTP/FTP ellipsoidal height	40.6
SBAS provider	1	FPAP latitude	691832.7385N
Airport identifier	ENAN	FPAP longitude	0160659.2420E
Runway	RW32	Threshold crossing height	50
Approach performance designator	0	TCH units	FT
Route indicator	-	Glide path angle	3.0
Reference path data selector	0	Course width at threshold	105
Reference path identifier	E32A	Length offset	0
LTP/FTP latitude	691716.5560N	Horizontal alert limit (HAL)	40
LTP/FTP longitude	0160904.8455E	Vertical alert limit (VAL)	50
	PRECISION APPROACH PATH CRC REMAINDER		915184ED