

ENHK GLS RWY 29 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	GOKKI	-	-	-12.0	-	-	-	A4100+	-	-	-	1.0
020	TF	HK402	-	-	-12.0	3.5	-	-	A3400+	K150-	-	-	1.0
010	IF	DUPPE	-	-	-12.0	-	-	-	A5000+	-	-	-	1.0
020	TF	HK403	-	-	-12.0	3.0	-	-	A4200+	-	-	-	1.0
030	TF	HK402	-	-	-12.0	3.0	-	-	A3400+	K150-	-	-	1.0
010	IF	VIDDE	-	-	-12.0	-	-	-	A5000+	-	-	-	1.0
020	TF	HK402	-	-	-12.0	4.5	-	-	A3400+	K150-	-	-	1.0
030	TF	HK401	-	-	-12.0	3.1	-	-	A2500+	-	-	-	1.0
040	TF	RW29	Y	-	-12.0	5.9	-	-	-	-	-3,9/50	-	0.3
060	FA	RW29	-	-	-12.0	-	-	-	A2000	-	-	-	1.0
070	DF	HK	-	-	-12.0	-	-	L	-	-	-	-	1.0
080	HM	HK	-	107 (118.8)	-12.0	1 MIN	-	R	A5000	-	-	-	1.0

Note: Recommended RNAV procedure coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
115.500 MHZ	702912.78N 0220832.60E	GND STN, VHF Antenna