

ENLK GLS RWY 20 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	IXOPO	-	-	-6.0	-	-	-	A4800+	-	-	-	1.0
020	TF	LK402	-	-	-6.0	5.0	-	-	A4000+	-	-	-	1.0
010	IF	ARVIM	-	-	-6.0	-	-	-	A4500+	-	-	-	1.0
020	TF	LK402	-	-	-6.0	5.0	-	-	A4000+	-	-	-	1.0
030	TF	LK401	-	-	-6.0	4.0	-	-	A4000+	-	-	-	1.0
040	TF	RW20	Y	-	-6.0	9.4	-	-	-	-	-3,9/49	-	-
050	TF	LK407	-	-	-6.0	2.0	-	-	-	K130-	-	-	1.0
060	TF	LK408	Y	-	-6.0	7.0	-	-	-	K130-	-	-	1.0
070	DF	SAD	-	-	-6.0	-	-	L	-	K130-	-	-	1.0
080	HM	SAD	-	355 (001.0)	-6.0	1 MIN	-	R	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
112.600 MHZ	680922.50N 0133636.40E	GND STN, VHF Antenna