

ENMH GLS RWY 17 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	NITNU	-	-	-15.0	-	-	-	A4000+	-	-	-	1.0
020	TF	MH401	-	-	-15.0	5.0	-	-	A2000+	-	-	-	1.0
010	IF	KOPES	-	-	-15.0	-	-	-	A4000+	-	-	-	1.0
020	TF	MH401	-	-	-15.0	5.0	-	-	A2000+	-	-	-	1.0
030	TF	MH400	-	-	-15.0	4.1	-	-	A2000+	-	-	-	1.0
040	TF	RW17	Y	-	-15.0	4.6	-	-	-	-	-3.9/49	-	-
050	TF	MH406	Y	-	-15.0	2.2	-	-	-	-	-	-	1.0
060	DF	KOPES	-	-	-15.0	-	-	L	-	-	-	-	1.0
070	HM	KOPES	-	348 (002.6)	-15.0	1 MIN	-	L	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
116.900 MHZ	710152.97N 0274951.81E	GND STN, VHF Antenna