

ENNM GLS RWY 07 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	BAKAR	-	-	-5.0	-	-	-	A4000+	-	-	-	1.0
020	TF	ULROP	-	-	-5.0	5.0	-	-	A3300+	-	-	-	1.0
010	IF	OTSEX	-	-	-5.0	-	-	-	A4000+	-	-	-	1.0
020	TF	ULROP	-	-	-5.0	5.0	-	-	A3300+	-	-	-	1.0
010	IF	GOPIG	-	-	-5.0	-	-	-	A4000+	-	-	-	1.0
020	TF	ULROP	-	-	-5.0	5.0	-	-	A3300+	-	-	-	1.0
030	TF	AMOSI	-	-	-5.0	5.0	-	-	A3000+	-	-	-	1.0
040	TF	RW07	Y	-	-5.0	7.0	-	-	-	-	-3.9/49	-	-
050	TF	NIPIX	-	-	-5.0	12.5	-	-	-	-	-	-	1.0
060	HM	NIPIX	-	250 (255.1)	-5.0	1 MIN	-	R	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
116.600 MHZ	642817.03N 0113352.91E	GND STN, VHF Antenna