

ENRM GLS RWY 04 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	GASKU	-	-	-4.0	-	-	-	A4000+	-	-	-	1.0
020	TF	EKNUS	-	-	-4.0	5.0	-	-	A3000+	-	-	-	1.0
010	IF	MIKDA	-	-	-4.0	-	-	-	A4000+	-	-	-	1.0
020	TF	EKNUS	-	-	-4.0	5.0	-	-	A3000+	-	-	-	1.0
010	IF	EKNUS	-	-	-4.0	-	-	-	A4000+	-	-	-	1.0
020	TF	RM401	-	-	-4.0	4.3	-	-	A3000+	-	-	-	1.0
030	TF	RW04	Y	-	-4.0	7.1	-	-	-	-	-3.9/49	-	-
040	CA	-	-	037 (041.3)	-4.0	-	-	-	A1500	-	-	-	1.0
050	DF	MIKDA	-	-	-4.0	-	-	R	-	-	-	-	1.0
060	HM	MIKDA	-	307 (311.3)	-4.0	1 MIN	-	R	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
115.600 MHZ	645013.92N 0110820.38E	GND STN, VHF Antenna