

ENSK GLS RWY 08 - RECOMMENDED CODING

| SN  | PD | WI    | Fly-over | °M (°T)     | MAG VAR | DIST (NM) | REC NAVAID | TD | ALT (FT) | Speed (KT) | VPA (°)/TCH (FT) | ARC CENTRE RADIUS (NM) | RNP (NM) |
|-----|----|-------|----------|-------------|---------|-----------|------------|----|----------|------------|------------------|------------------------|----------|
| 010 | IF | SK534 | -        | -           | -7.0    | -         | -          | -  | A5200+   | -          | -                | -                      | 1.0      |
| 020 | TF | UDANU | -        | -           | -7.0    | 5.0       | -          | -  | A4000+   | -          | -                | -                      | 1.0      |
| 030 | TF | SK532 | -        | -           | -7.0    | 4.0       | -          | -  | A3500+   | -          | -                | -                      | 1.0      |
| 040 | TF | RW08  | Y        | -           | -7.0    | 8.2       | -          | -  | -        | -          | -3.9/49          | -                      | -        |
| 050 | CA | -     | Y        | 084 (091.0) | -7.0    | -         | -          | -  | A1000    | -          | -                | -                      | 1.0      |
| 060 | CF | KG    | -        | 050 (057.2) | -7.0    | -         | -          | L  | -        | -          | -                | -                      | 1.0      |
| 070 | FA | KG    | -        | 050 (057.0) | -7.0    | -         | -          | -  | A3300    | -          | -                | -                      | 1.0      |
| 080 | DF | KG    | -        | -           | -7.0    | -         | -          | L  | -        | -          | -                | -                      | 1.0      |
| 090 | HM | KG    | -        | 234 (241.0) | -7.0    | 1 MIN     | -          | R  | A5000    | -          | -                | -                      | 1.0      |

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

SCAT-I FREQUENCY AND POSITION

| FREQUENCY   | POSITION                  | REMARK                  |
|-------------|---------------------------|-------------------------|
| 115.700 MHZ | 683455.24N<br>0150128.24E | GND STN, VHF<br>Antenna |