

ENST GLS RWY 20 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAV AID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	BOXDI	-	-	-5.0	-	-	-	A4600+	-	-	-	1.0
20	TF	ST430	-	-	-5.0	4.2	-	-	A3500+	-	-	-	1.0
10	IF	PUMNU	-	-	-5.0	-	-	-	A5000+	-	-	-	1.0
20	TF	ST430	-	-	-5.0	4.2	-	-	A3500+	-	-	-	1.0
10	IF	NIKGE	-	-	-5.0	-	-	-	A4600+	-	-	-	1.0
20	TF	ST430	-	-	-5.0	4.2	-	-	A3500+	-	-	-	1.0
30	TF	ST431	-	-	-5.0	4.5	-	-	A2500+	-	-	-	1.0
40	TF	RW20	Y	-	-5.0	6.9	-	-	-	-	-3.2/49	-	-
50	CA	-	-	200 (204.9)	-5.0	-	-	-	A1400+	-	-	-	1.0
60	DF	UGMAL	-	-	-5.0	-	-	R	-	-	-	-	1.0
70	HM	UGMAL	-	265 (269.9)	-5.0	1 MIN	-	R	A5000	K170-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
114.300 MHZ	655722.00N 0122812.61E	GND STN, VHF Antenna