

ENBS GLS RWY 21 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	LUNUX	-	-	-16.0	-	-	-	A4000+	-	-	-	1.0
020	TF	NAMAP	-	-	-16.0	5.0	-	-	A3000+	-	-	-	1.0
010	IF	OLADU	-	-	-16.0	-	-	-	A4000+	-	-	-	1.0
020	TF	NAMAP	-	-	-16.0	5.0	-	-	A3000+	-	-	-	1.0
030	TF	BS501	-	-	-16.0	4.1	-	-	A3000+	-	-	-	1.0
040	TF	RW21	-	-	-16.0	5.9	-	-	-	-	-3.9/49	-	-
050	CA	-	-	208 (224.0)	-16.0	-	-	-	A2000	-	-	-	1.0
060	DF	LUNUX	-	-	-16.0	-	-	R	-	-	-	-	1.0
070	HM	LUNUX	-	118 (134.0)	-16.0	1 MIN	-	L	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
115.000 MHZ	703558.70N 0294111.93E	GND STN, VHF Antenna