

ENML STAR RWY 25 (RNAV) - ROUTES

- GENERAL:

Surveillance service shall be available
- LOSS OF RNAV CAPABILITY:

Request vectoring.
- VECTORIZING:

Vectoring may be used for sequencing.
- RADIO COMMUNICATION FAILURE:

Squawk A7600. Proceed on STAR and make APCH to RWY 25

DESIGNATOR	ROUTE	RESTRICTIONS	DESCEND	CLEARANCE LIMIT
BASTU 1M  (BASTU ONE MIKE ARRIVAL)	From BASTU, to EPZAG, to EVLED, to ML624, to ERPER.	Cross BASTU at or above FL 140. Cross EPZAG at or above FL 120. Cross EVLED at or above 10 000 FT. Cross ML624 at or above 7000 FT. Cross ERPER at or above 5000 FT.	As cleared by ATC.	ERPER
DEKEB 2M  (DEKEB TWO MIKE ARRIVAL)	From DEKEB, to IRGAD, to GUDVA, to UTILU.	Cross GUDVA at or above 7000 FT. Cross UTILU at or above 5000 FT.	As cleared by ATC.	UTILU
OBITI 2M  (OBITI TWO MIKE ARRIVAL)	From OBITI, to ARNEN, to ML620, to ERPER.	Cross OBITI at or above FL 140. Cross ARNEN at or above 10 000 FT. Cross ML620 at or above 7000 FT. Cross ERPER at or above 5000 FT.	As cleared by ATC.	ERPER
TUMIM 3M  (TUMIM THREE MIKE ARRIVAL)	From TUMIM, to ML621, to ARNEN, to ML620, to ERPER.	Cross TUMIM at or above FL 120. Cross ML621 at or above FL 100. Cross ARNEN at or above FL 100. Cross ML620 at or above 7000 FT. Cross ERPER at or above 5000 FT.	As cleared by ATC.	ERPER
VEPUL 2M  (VEPUL TWO MIKE ARRIVAL)	From VEPUL, to ML622, to SUMIP, to ML623, to ERPER.	Cross VEPUL at or above FL 140. Cross ML622 at or above 10 000 FT. Cross SUMIP at or above 9000 FT. Cross ML623 at or above 7000 FT. Cross ERPER at or above 5000 FT.	As cleared by ATC.	ERPER