

ENHF OMNI-DIRECTIONAL DEPARTURE RWY 22

REMARKS:

CAT A, B only.

RADIO COMMUNICATION FAILURE:

Squawk A7600. Climb on track 238° to 4500 FT, then proceed in the most direct manner possible to join the CPL route, climbing to CPL cruising LVL. ACFT under vectoring shall, after set transponder to A7600, proceed the most direct route to join the CPL route, climbing to the CPL cruising LVL.

CLOSE-IN OBSTACLES:

Rising terrain and artificial obstacles between THR RWY 04 and 0.2 NM from THR RWY 04 require more than 3.6% climb gradient, and must be avoided visually or by other means.

VECTORIZING/
DIRECT ROUTING:

When being vectored or cleared for DCT routing, the climb gradient(s) stated in Omni-directional departure “RESTRICTIONS”-table apply.

ATC CLEARANCE:

Departing IFR flights shall obtain ATC clearance from HAMMERFEST INFORMATION.

MAGNETIC VARIATION:

13°E (2020)

DESIGNATOR	ROUTE	RESTRICTIONS	CLIMB TO	CONTACT
OMNI-DIRECTIONAL DEPARTURE 2D (ENHF2D)	Climb on track 238°. Expect further clearance from ATC.	MNM climb gradient 3.6% (219 FT/NM) to 4500 FT. If unable to comply, inform ATC.	As cleared by ATC.	As instructed by HAMMERFEST INFORMATION