

ENSB RNP Z RWY 27 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	NAXEN	-	-	-10.0	-	-	-	A5000+	K230-	-	-	1.0
020	TF	XESLA	-	-	-10.0	5.0	-	-	A5000+	K220-	-	-	1.0
010	IF	RARAG	-	-	-10.0	-	-	-	A5100+	K230-	-	-	1.0
020	TF	XESLA	-	-	-10.0	5.0	-	-	A5000+	K220-	-	-	1.0
010	IF	XESLA	-	-	-10.0	-	-	-	A5000+	K220-	-	-	1.0
020	TF	SB700	-	-	-10.0	4.8	-	-	A5000+	-	-	-	1.0
030	TF	SB701	Y	-	-10.0	9.6	-	-	-	-	-3.6/50	-	0.3
040	TF	SB702	Y	-	-10.0	9.1	-	-	-	-	-	-	1.0
050	DF	NAXEN	-	-	-10.0	-	-	R	A5000	-	-	-	1.0
060	HM	NAXEN	-	222 (232.2)	-10.0	1 MIN	-	L	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.