

ENRY RNP RWY 12 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	OLIXA	-	-	-4.0	-	-	-	A3000+		-	-	1.0
020	TF	RENLI	-	-	-4.0	5.4	-	-	A3000+		-	-	1.0
010	IF	ASREL	-	-	-4.0	-	-	-	A3000+		-	-	1.0
020	TF	RENLI	-	-	-4.0	5.4	-	-	A3000+		-	-	1.0
010	IF	ALOXI	-	-	-4.0	-	-	-	A3000+		-	-	1.0
020	TF	RENLI	-	-	-4.0	5.0	-	-	A3000+		-	-	1.0
030	TF	DEKOS	-	-	-4.0	5.2	-	-	A3000+		-	-	1.0
040	TF	RW12	Y	-	-4.0	8.8	-	-	-		-3.0/50	-	0.3
050	TF	RY401	Y	-	-4.0	11.1	-	-	A3000-		-	-	1.0
060	DF	YG	-	-	-4.0	-	-	L	-	K215-	-	-	1.0
070	HM	YG	-	112 (116.0)	-4.0	1 MIN	-	L	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: The use of SBAS/GNSS geometric altitude as a source of altitude for approaches to LNAV/VNAV minima is permitted only for aircraft specifically certified for this type of operation. See “EASA CS ACNS.C.PBN.560” for additional information.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.

Note: DEKOS holding not included in standard APCH transitions