

ENZV RNP N RWY 18 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	KOPPO	-	-	-2.0	-	-	-	A3000+	K220-	-	-	1.0
20	TF	ZV112	-	-	-2.0	2.8	-	-	A2000+	-	-	-	1.0
30	RF	ZV110	-	-	-2.0	3.0	-	L	A1500+	-	-	ZV003 3.000	1.0
40	RF	ZV111	-	-	-2.0	2.2	-	R	-	-	-3.0	ZV002 2.000	0.3
50	TF	RW18	Y	-	-2.0	2.3			-	-	-3.0/50	-	0.3
60	TF	YOFUF	-	-	-2.0	15.0	-	-	-	-	-	-	1.0
70	HM	YOFUF	-	177 (179.1)	-2.0	1 MIN	-	R	A3000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.