

ENZV RNP E RWY 36 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	ISUDE	-	-	-2.0	-	-	-	A3000+	K220-	-	-	1.0
20	TF	ZV340	-	-	-2.0	2.5	-	-	A2500+	-	-	-	1.0
30	TF	ZV341	-	-	-2.0	1.8	-	-	A2000+	-	-	-	0.7
40	TF	ZV342	-	-	-2.0	1.3	-	-	A1700+	-	-	-	0.5
50	RF	ZV333	-	-	-2.0	3.0	-	R	-	-	-3.0	ZV011 2.100	0.3
60	TF	RW36	Y	-	-2.0	2.1	-	-	-	-	-3.0/50	-	0.3
70	TF	EGOKE	-	-	-2.0	15.0	-	-	-	-	-	-	1.0
80	HM	EGOKE	-	357 (359.1)	-2.0	1 MIN	-	L	A3000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.