

ENRO RNP RWY 31 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	EMDEG	-	-	-4.0	-	-	-	A6300+	K230-	-	-	1.0
20	TF	UMBUP	-	-	-4.0	5.0	-	-	A5300+	K210-	-	-	1.0
10	IF	TUVUT	-	-	-4.0	-	-	-	A5300+	-	-	-	1.0
20	TF	UMBUP	-	-	-4.0	5.0	-	-	A5300+	K210-	-	-	1.0
10	IF	UMBUP	-	-	-4.0	-	-	-	A5300+	K210-	-	-	1.0
20	TF	KUVUM	-	-	-4.0	4.1	-	-	A4500+	-	-	-	1.0
30	TF	RO400	Y	-	-4.0	6.8	-	-	-	-	-3.3/-	-	0.3
40	TF	RO401	Y	-	-4.0	2.9	-	-	-	-	-	-	1.0
50	DF	UMBUP	-	-	-4.0	-	-	R	A5300	-	-	-	1.0
60	HM	UMBUP	-	313 (317.0)	-4.0	6.2	-	L	A5300	K210-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.