

ENVD GLS RWY 07 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	RUDUP	-	-	-16.0	-	-	-	A3000+	-	-	-	1.0
020	TF	EPOPU	-	-	-16.0	5.0	-	-	A3000+	-	-	-	1.0
010	IF	ULSAK	-	-	-16.0	-	-	-	A3000+	-	-	-	1.0
020	TF	EPOPU	-	-	-16.0	5.0	-	-	A3000+	-	-	-	1.0
010	IF	EPOPU	-	-	-16.0	-	-	-	A3000+	-	-	-	1.0
020	TF	VD407	-	-	-16.0	4.0	-	-	A2000+	-	-	-	1.0
030	TF	RW07	Y	-	-16.0	4.4	-	-	-	-	-3.9/49	-	-
040	TF	TOKLA	-	-	-16.0	9.0	-	-	-	-	-	-	1.0
050	HM	TOKLA	-	252 (267.8)	-16.0	1 MIN	-	L	A3000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.

Note: EPOPU holding not included in standard APCH transitions.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
115.600 MHZ	700359.43N 0294958.85E	GND STN, VHF Antenna