

ENVD GLS RWY 25 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	AGDIR	-	-	-16.0	-	-	-	A3000+	-	-	-	1.0
020	TF	TOKLA	-	-	-16.0	5.0	-	-	A3000+	-	-	-	1.0
010	IF	RULAX	-	-	-16.0	-	-	-	A3000+	-	-	-	1.0
020	TF	TOKLA	-	-	-16.0	5.0	-	-	A3000+	-	-	-	1.0
010	IF	TOKLA	-	-	-16.0	-	-	-	A3000+	-	-	-	1.0
020	TF	VD506	-	-	-16.0	4.0	-	-	A2000+	-	-	-	1.0
030	TF	RW25	Y	-	-16.0	4.5	-	-	-	-	-3.9/49	-	-
040	TF	EPOPU	-	-	-16.0	8.9	-	-	-	-	-	-	1.0
050	HM	EPOPU	-	071 (087.1)	-16.0	1 MIN	-	L	A3000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: TOKLA holding not included in standard APCH transitions.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
115.600 MHZ	700359.43N 0294958.85E	GND STN, VHF Antenna