

ENVD RNP Z RWY 25 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	AGDIR	-	-	-16.0	-	-	-	A3000+	-	-	-	1.0
020	TF	TOKLA	-	-	-16.0	5.0	-	-	A3000+	-	-	-	1.0
010	IF	RULAX	-	-	-16.0	-	-	-	A3000+	-	-	-	1.0
020	TF	TOKLA	-	-	-16.0	5.0	-	-	A3000+	-	-	-	1.0
010	IF	TOKLA	-	-	-16.0	-	-	-	A3000+	-	-	-	1.0
020	TF	VD506	-	-	-16.0	4.0	-	-	A2000+	-	-	-	1.0
030	TF	RW25	Y	-	-16.0	4.5	-	-	-	-	-3.9/50	-	0.3
040	TF	EPOPU	-	-	-16.0	-	-	-	-	-	-	-	1.0
050	HM	EPOPU	-	071 (087.1)	-16.0	1 MIN	-	L	A3000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: The use of SBAS/GNSS geometric altitude as a source of altitude for approaches to LNAV/VNAV minima is permitted only for aircraft specifically certified for this type of operation. See “EASA CS ACNS.C.PBN.560” for additional information.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.

Note: TOKLA holding, not included in standard APCH transitions.