I

I

I

ENGM STAR RWY 01L/R (RNAV) – ROUTES

GENERAL:	Surveillance service shall be available.
GENERAL.	Maximum speed 250 KT IAS unless otherwise stated under RESTRICTIONS or instructed by ATC.
	ESEBA STAR: TEKVA holding (left turn) is associated with ESEBA STAR. TEKVA holding is published in AIP Sweden ENR 3.6
LOSS OF RNAV CAPABILITY:	Request vectoring.
VECTORING:	Vectoring may be used for sequencing.
RADIO COMMUNICATION FAILURE:	Squawk A7600. Follow cleared or expected STAR until IAF, then start approach to assigned runway without delay. If no specific runway for landing has been assigned, start approach to runway 01R without delay.

DESIGNATOR	ROUTE	RESTRICTIONS	DESCEND	CLEARANCE LIMIT
ADOPI 3L (ADOPI THREE LIMA ARRIVAL)	From ADOPI to NIVDU, to GM402, to GM405, to GM406, to GM404, to GM455, turn left to VALPU	Speed 250 KT IAS or less: ADOPI, NIVDU. Speed 220 KT IAS or less: GM402, GM405, GM406, GM404, GM455, VALPU. Cross GM402 and GM455 at FL100. Cross VALPU at 5000 FT or above.	As cleared by ATC	VALPU HLDG
BELGU 3L (BELGU THREE LIMA ARRIVAL)	From BELGU to VANUK, to GM456, to GM400, to GM402, to GM405, to GM406, to GM404, to GM455, turn left to VALPU	Speed 250 KT IAS or less: BELGU, VANUK, GM456, GM400. Speed 220 KT IAS or less: GM402, GM405, GM406, GM404, GM455, VALPU. Cross GM456 at or below FL120. Cross GM400 and GM455 at FL090. Cross VALPU at 5000 FT or above.	As cleared by ATC	VALPU HLDG
ESEBA 4L (ESEBA FOUR LIMA ARRIVAL)	From ESEBA to IDAMO, to GM403, to GM411, to GM413, to GM412, to GM454, turn right to INSUV	Speed 250 KT IAS or less: ESEBA, IDAMO. Speed 220 KT IAS or less: GM403, GM411, GM413, GM413, GM412, GM454, INSUV. Cross GM403 and GM454 at FL100 Cross INSUV at 5000 FT or above. Note: See information pertaining to TEKVA holding above.	As cleared by ATC	INSUV HLDG
INREX 4L (INREX FOUR LIMA ARRIVAL)	From INREX to SUSIB, to GM457, to GM401, to GM403, to GM411, to GM413, to GM412, to GM454, turn right to INSUV	Speed 250 KT IAS or less: INREX, SUSIB, GM457, GM401. Speed 220 KT IAS or less: GM403, GM411, GM413, GM412, GM454, INSUV. Cross GM457 at or below FL120. Cross GM401 and GM454 at FL090. Cross INSUV at 5000 FT or above.	As cleared by ATC	INSUV HLDG