

ENGM RNP W RWY 01L (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	ELVUN	-	-	-4.0	-	-	-	A5000+	K220-	-	-	1.0
20	TF	GM550	-	-	-4.0	4.8	-	-	A4000+	K210-	-	-	1.0
30	RF	GM600	-	-	-4.0	1.9	-	L	A3500+	-	-	GM005 3.400	0.8
40	RF	GM551	-	-	-4.0	1.4	-	L	A3000+	-	-	GM005 3.400	0.3
50	TF	GM552	-	-	-4.0	1.9	-	-	A2400+	K205-	-	-	0.3
60	RF	GM553	-	-	-4.0	2.0	-	L	A1800+	-	-	GM006 3.000	0.3
70	TF	RW01L	-	-	-4.0	3.4	-	-	-	-	-3.0/50	-	0.3
80	TF	GM918	Y	-	-4.0	21.1	-	-	-	-	-	-	1.0
90	DF	GRM	-	-	-4.0	-	-	L	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

RF arc centre coordinates:

RF arc centre identifier	Latitude	Longitude
GM005	600754.19N	0105313.09E
GM006	600839.82N	0105646.91E