

ENRY STAR RWY 30 (RNAV) - ROUTES

- GENERAL:

Surveillance service shall be available
- LOSS OF RNAV CAPABILITY:

Request vectoring.
- VECTORIZING:

Vectoring may be used for sequencing.
- RADIO COMMUNICATION FAILURE:

Squawk A7600. Proceed on STAR and make APCH to RWY 30.

DESIGNATOR	ROUTE	RESTRICTIONS	DESCEND	CLEARANCE LIMIT
<b>BAMIX 7R</b>  (BAMIX SEVEN ROMEO ARRIVAL)	From BAMIX to RY803, to RY807, to UXOBA.	Cross BAMIX at or above 4000 FT. Cross RY803 between 4000 FT and FL 110. Cross RY807 at or above 3000 FT. Cross UXOBA at or above 3000 FT.	As cleared by ATC.	UXOBA
<b>ESOSI 8R</b>  (ESOSI EIGHT ROMEO ARRIVAL)	From ESOSI to NENIX, to XAMUL.	Cross ESOSI at or above 5000 FT. Cross NENIX at or above 5000 FT. Cross XAMUL at or above 3000 FT.	As cleared by ATC.	XAMUL
<b>REGMA 7R</b>  (REGMA SEVEN ROMEO ARRIVAL)	From REGMA to RY850, to RIGBU.	Cross REGMA at or above 5000 FT. Cross RY850 at or above 5000 FT. Cross RIGBU at or above 3000 FT.	As cleared by ATC.	RIGBU
<b>ULMUG 8R</b>  (ULMUG EIGHT ROMEO ARRIVAL)	From ULMUG to XAMUL.	Cross ULMUG between 5000 FT and FL 150. Cross XAMUL at or above 5000 FT.	As cleared by ATC.	XAMUL
<b>VATEX 7R</b>  (VATEX SEVEN ROMEO ARRIVAL)	From VATEX to RIGBU.	Cross VATEX at or above 4000 FT. Cross RIGBU at or above 4000 FT.	As cleared by ATC.	RIGBU