

ENGM RNP N RWY 19R (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	RIRUT	-	-	-4.0	-	-	-	A5000+	K220-	-	-	1.0
20	TF	GM601	-	-	-4.0	4.1	-	-	A4500+	-	-	-	1.0
30	TF	GM564	-	-	-4.0	3.1	-	-	A3300+	-	-	-	0.3
40	TF	GM563	-	-	-4.0	2.3	-	-	A2500+	-	-	-	0.3
50	RF	GM562	-	-	-4.0	2.4	-	R	A1800+	-	-	GM004 5.718	0.3
60	TF	RW19R	-	-	-4.0	3.4	-	-	-	-	-3.0/50	-	0.3
70	TF	GM995	Y	-	-4.0	2.7	-	-	-	-	-	-	1.0
80	CF	GM996	Y	223 (227.0)	-4.0	-	-	R	-	-	-	-	1.0
90	DF	GRM	-	-	-4.0	-	-	R	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

RF arc centre coordinates:

RF arc centre identifier	Latitude	Longitude
GM004	601747.61N	0105620.59E