

ENHK RNP RWY 29 - RECOMMENDED CODING

| SN  | PD | WI    | Fly-over | °M (°T)     | MAG VAR | DIST (NM) | REC NAVAID | TD | ALT (FT) | Speed (KT) | VPA (°)/ TCH (FT) | ARC CENTRE RADIUS (NM) | RNP (NM) |
|-----|----|-------|----------|-------------|---------|-----------|------------|----|----------|------------|-------------------|------------------------|----------|
| 010 | IF | GOKKI | -        | -           | -12.0   | -         | -          | -  | A4100+   | -          | -                 | -                      | 1.0      |
| 020 | TF | HK402 | -        | -           | -12.0   | 3.5       | -          | -  | A3400+   | K150-      | -                 | -                      | 1.0      |
| 010 | IF | DUPPE | -        | -           | -12.0   | -         | -          | -  | A5000+   | -          | -                 | -                      | 1.0      |
| 020 | TF | HK403 | -        | -           | -12.0   | 3.0       | -          | -  | A4200+   | -          | -                 | -                      | 1.0      |
| 030 | TF | HK402 | -        | -           | -12.0   | 3.0       | -          | -  | A3400+   | K150-      | -                 | -                      | 1.0      |
| 010 | IF | VIDDE | -        | -           | -12.0   | -         | -          | -  | A5000+   | -          | -                 | -                      | 1.0      |
| 020 | TF | HK402 | -        | -           | -12.0   | 4.5       | -          | -  | A3400+   | K150-      | -                 | -                      | 1.0      |
| 030 | TF | HK401 | -        | -           | -12.0   | 3.1       | -          | -  | A2500+   | -          | -                 | -                      | 1.0      |
| 040 | TF | RW29  | Y        | -           | -12.0   | 5.9       | -          | -  | -        | -          | -3.9/50           | -                      | 0.3      |
| 050 | TF | HK406 | Y        | -           | -12.0   | 6.1       | -          | -  | -        | -          | -                 | -                      | 1.0      |
| 060 | DF | HK    | -        | -           | -12.0   | -         | -          | L  | -        | -          | -                 | -                      | 1.0      |
| 070 | HM | HK    | -        | 107 (118.8) | -12.0   | 1 MIN     | -          | R  | A5000    | -          | -                 | -                      | 1.0      |

Note: Recommended RNAV procedure coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: The use of SBAS/GNSS geometric altitude as a source of altitude for approaches to LNAV/VNAV minima is permitted only for aircraft specifically certified for this type of operation. See "EASA CS ACNS.C.PBN.560" for additional information.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 200 FT shall not be used due to approach operation Type B limitations.

FAS DB

|                                       |               |                              |               |
|---------------------------------------|---------------|------------------------------|---------------|
| Operation type                        | 0             | LTP/FTP ellipsoidal height   | 32.4          |
| SBAS provider                         | 1             | FPAP latitude                | 702946.7380N  |
| Airport identifier                    | ENHK          | FPAP longitude               | 0220514.3485E |
| Runway                                | RW29          | Threshold crossing height    | 50            |
| Approach performance designator       | 0             | TCH units                    | FT            |
| Route indicator                       | -             | Glide path angle             | 3.9           |
| Reference path data selector          | 0             | Course width at threshold    | 105           |
| Reference path identifier             | E29A          | Length offset                | 1768          |
| LTP/FTP latitude                      | 702904.8045N  | Horizontal alert limit (HAL) | 40            |
| LTP/FTP longitude                     | 0220902.2915E | Vertical alert limit (VAL)   | 35            |
|                                       |               |                              |               |
| PRECISION APPROACH PATH CRC REMAINDER |               |                              | 01DC7BBA      |