

ENSR RNP-A - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	INLAM	-	-	-11.0	-	-	-	A5000+	-	-	-	1.0
020	TF	NEROD	-	-	-11.0	5.0	-	-	A5000+	-	-	-	1.0
010	IF	SOTOP	-	-	-11.0	-	-	-	A5000+	-	-	-	1.0
020	TF	NEROD	-	-	-11.0	5.0	-	-	A5000+	-	-	-	1.0
010	IF	SUSIN	-	-	-11.0	-	-	-	A5000+	-	-	-	1.0
020	TF	NEROD	-	-	-11.0	4.2	-	-	A5000+	-	-	-	1.0
030	TF	SR501	-	-	-11.0	5.9	-	-	A3400+	-	-	-	1.0
040	TF	SR502	Y	-	-11.0	5.4	-	-	-	-	-3.1/-	-	0.3
050	DF	SR501	-	-	-11.0	-	-	R	-	-	-	-	1.0
060	TF	NEROD	-	-	-11.0	5.9	-	-	A5000	-	-	-	1.0
070	CA	-	-	002 (013.1)	-11.0	-	-	-	A5000	-	-	-	1.0
080	DF	NEROD	-	-	-11.0	-	-	R	A5000	-	-	-	1.0
090	HM	NEROD	-	208 (219.2)	-11.0	1 MIN	-	L	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: NEROD holding not included in standard APCH transitions.