

ENEV RNP Z RWY 35 - RECOMMENDED CODING

| SN  | PD | WI    | Fly-over | °M (°T)     | MAG VAR | DIST (NM) | REC NAVAID | TD | ALT (FT) | Speed (KT) | VPA (°)/TCH (FT) | ARC CENTRE RADIUS (NM) | RNP (NM) |
|-----|----|-------|----------|-------------|---------|-----------|------------|----|----------|------------|------------------|------------------------|----------|
| 010 | IF | LEGLU | -        | -           | -8.0    | -         | -          | -  | A7000+   | -          | -                | -                      | 1.0      |
| 020 | TF | STETI | -        | -           | -8.0    | 8.0       | -          | -  | A7000+   | K220-      | -                | -                      | 1.0      |
| 010 | IF | MAXED | -        | -           | -8.0    | -         | -          | -  | A7000+   | -          | -                | -                      | 1.0      |
| 020 | TF | STETI | -        | -           | -8.0    | 7.4       | -          | -  | A7000+   | K220-      | -                | -                      | 1.0      |
| 010 | IF | STETI | -        | -           | -8.0    | -         | -          | -  | A7000+   | K220-      | -                | -                      | 1.0      |
| 020 | TF | EV712 | -        | -           | -8.0    | 10.6      | -          | -  | A3800+   | -          | -                | -                      | 1.0      |
| 030 | TF | EV710 | Y        | -           | -8.0    | 8.1       | -          | -  | -        | -          | -3.9/50          | -                      | 0.3      |
| 040 | TF | FS    | -        | -           | -8.0    | 7.9       | -          | -  | -        | K185-      | -                | -                      | 1.0      |
| 050 | FA | FS    | -        | 351 (358.7) | -8.0    | -         | -          | -  | A3800+   | -          | -                | -                      | 1.0      |
| 060 | DF | FS    | -        | -           | -8.0    | -         | -          | L  | -        | -          | -                | -                      | 1.0      |
| 070 | HM | FS    | -        | 171 (178.6) | -8.0    | 1 MIN     | -          | R  | A5000    | K210-      | -                | -                      | 1.0      |

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.