

ENSG RNP Y RWY 24 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	BEDGO	-	-	-2.0	-	-	-	A6900+	-	-	-	1.0
020	TF	BANEN	-	-	-2.0	5.0	-	-	A6300+	K150-	-	-	1.0
010	IF	DEVUK	-	-	-2.0	-	-	-	A7100+	-	-	-	1.0
020	TF	BANEN	-	-	-2.0	5.0	-	-	A6300+	K150-	-	-	1.0
010	IF	BANEN	-	-	-2.0	-	-	-	A6300+	K150-	-	-	1.0
020	TF	TUPOG	-	-	-2.0	3.2	-	-	A5600+	-	-	-	1.0
030	TF	SG403	Y	-	-2.0	6.7	-	-	-	K130-	-4.0/50	-	0.3
040	CF	SG404	-	210 (211.9)	-2.0	-	SOG	-	-	-	-	-	1.0
050	TF	VNG	-	-	-2.0	14.0	-	-	-	-	-	-	1.0
060	HM	VNG	-	062 (064.4)	-2.0	1 MIN	-	L	A6500	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.