

ENAL RNP Y RWY 06 (LPV only) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	LAPEV	-	-	-2.0	-	-	-	A5000+	-	-	-	1.0
020	TF	UVEVA	-	-	-2.0	7.0	-	-	A3000+	K230-	-	-	1.0
010	IF	ASKEK	-	-	-2.0	-	-	-	A3000+	K230-	-	-	1.0
020	TF	UVEVA	-	-	-2.0	5.0	-	-	A3000+	K230-	-	-	1.0
010	IF	UVEVA	-	-	-2.0	-	-	-	A3000+	K230-	-	-	1.0
020	TF	ATBOL	-	-	-2.0	4.4	-	-	A3000+	-	-	-	1.0
030	TF	RW06	Y	-	-2.0	6.6	-	-	-	-	-3.4/50	-	-
040	TF	AL822	Y	-	-2.0	2.1	-	-	-	K185-	-	-	0.3
050	TF	AL821	Y	-	-2.0	4.4	-	-	-	K185-	-	-	1.0
060	DF	TOMNO	-	-	-2.0	-	-	L	-	K185-	-	-	1.0
070	HM	TOMNO	-	328 (329.5)	-2.0	-	-	R	A5000	K220-	-	-	1.0

Note: ATBOL holding not included in standard APCH transitions.

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: The use of SBAS/GNSS geometric altitude as a source of altitude for approaches to LNAV/VNAV minima is permitted only for aircraft specifically certified for this type of operation. See “EASA CS ACNS.C.PBN.560” for additional information.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 200 FT shall not be used due to approach operation Type B limitations.

FAS DB

Operation type	0	LTP/FTP ellipsoidal height	55.5
SBAS provider	1	FPAP latitude	623353.3315N
Airport identifier	ENAL	FPAP longitude	0060749.7990E
Runway	RW06	Threshold crossing height	50
Approach performance designator	0	TCH units	FT
Route indicator	Y	Glide path angle	3.4
Reference path data selector	0	Course width at threshold	105
Reference path identifier	E06A	Length offset	0
LTP/FTP latitude	623323.4110N	Horizontal alert limit (HAL)	40
LTP/FTP longitude	0060532.8900E	Vertical alert limit (VAL)	35
	PRECISION APPROACH PATH CRC REMAINDER		54680A90