

ENGM RNP O RWY 01R (AR) - RECOMMENDED CODING

| SN  | PD | WI    | Fly-over | °M(°T) | MAG VAR | DIST (NM) | REC NAVAID | TD | ALT (FT) | Speed (KT) | VPA(°)/ TCH(FT) | ARC CENTRE RADIUS (NM) | RNP (NM) |
|-----|----|-------|----------|--------|---------|-----------|------------|----|----------|------------|-----------------|------------------------|----------|
| 010 | IF | SIFOZ | -        | -      | -4.0    | -         | -          | -  | A5000+   | K220-      | -               | -                      | RNP 0.8  |
| 020 | TF | GM640 | -        | -      | -4.0    | 2.2       | -          | -  | A4000+   | -          | -               | -                      | RNP 0.8  |
| 030 | RF | GM641 | -        | -      | -4.0    | 1.6       | -          | R  | -        | -          | -               | GM015 6.650            | RNP 0.7  |
| 040 | TF | GM642 | -        | -      | -4.0    | 2.3       | -          | -  | A3500+   | K195-      | -               | -                      | RNP 0.7  |
| 050 | RF | GM643 | -        | -      | -4.0    | 2.0       | -          | R  | -        | -          | -               | GM016 2.899            | RNP 0.7  |
| 060 | RF | GM644 | -        | -      | -4.0    | 1.3       | -          | R  | A2500+   | K185-      | -               | GM014 10.837           | RNP 0.5  |
| 070 | RF | GM558 | -        | -      | -4.0    | 2.7       | -          | L  | A1800+   | -          | -               | GM017 2.473            | RNP 0.5  |
| 080 | TF | RW01R | -        | -      | -4.0    | 3.4       | -          | -  | -        | -          | -3.0/50         | -                      | RNP 0.3  |
| 090 | TF | GM917 | Y        | -      | -4.0    | 2.7       | -          | -  | -        | -          | -               | -                      | RNP 1.0  |
| 100 | DF | NIDIM | Y        | -      | -4.0    | -         | -          | R  | A4000    | -          | -               | -                      | RNP 1.0  |
| 110 | DF | GRM   | -        | -      | -4.0    | -         | -          | R  | A4000    | -          | -               | -                      | RNP 1.0  |

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: The use of SBAS/GNSS geometric altitude as a source of altitude for approaches to LNAV/VNAV minima is permitted only for aircraft specifically certified for this type of operation. See “EASA CS ACNS.C.PBN.560” for additional information.

RF arc centre coordinates:

| RF arc centre identifier | Latitude   | Longitude   |
|--------------------------|------------|-------------|
| GM014                    | 595454.81N | 0110440.69E |
| GM015                    | 595829.65N | 0110349.24E |
| GM016                    | 600228.73N | 0110001.51E |
| GM017                    | 600757.92N | 0105950.18E |