

ENNA STAR RWY 34 (RNAV) - ROUTES

- GENERAL:

Surveillance service shall be available
- LOSS OF RNAV CAPABILITY:

Request vectoring.
- VECTORIZING:

Vectoring may be used for sequencing.
- RADIO COMMUNICATION FAILURE:

Squawk A7600. Proceed on STAR and make APCH to RWY 34

DESIGNATOR	ROUTE	RESTRICTIONS	DESCEND	CLEARANCE LIMIT
ABANU 1M (ABANU ONE MIKE ARRIVAL)	From ABANU to RENBU.	Cross ABANU at or above FL110 Cross RENBU at or above 4300 FT. MAX 230 KT IAS at RENBU.	As cleared by ATC.	RENBU.
LAPVI 1M (LAPVI ONE MIKE ARRIVAL)	From LAPVI to ODVIG.	Cross ODVIG at or above 4800 FT. MAX 230 KT IAS at ODVIG.	As cleared by ATC.	ODVIG.
LUVED 1M (LUVED ONE MIKE ARRIVAL)	From LUVED to NA415. To ODVIG.	Cross LUVED at or above FL120 Cross NA415 at or above 7000 FT. Cross ODVIG at or above 4300 FT. MAX 230 KT IAS at ODVIG.	As cleared by ATC.	ODVIG.