

ENSD RNP RWY 26 - RECOMMENDED CODING

| SN  | PD | WI    | Fly-over | °M(°T)      | MAG VAR | DIST (NM) | REC NAVAID | TD | ALT (FT) | Speed (KT) | VPA(°)/ TCH(FT) | ARC CENTRE RADIUS (NM) | RNP (NM) |
|-----|----|-------|----------|-------------|---------|-----------|------------|----|----------|------------|-----------------|------------------------|----------|
| 010 | IF | OGDIT | -        | -           | -2.0    | -         | -          | -  | A6800+   | -          | -               | -                      | 1.0      |
| 020 | TF | ITVAK | -        | -           | -2.0    | 4.0       | -          | -  | A6800+   | -          | -               | -                      | 1.0      |
| 010 | IF | GIGMU | -        | -           | -2.0    | -         | -          | -  | A6800+   | -          | -               | -                      | 1.0      |
| 020 | TF | ITVAK | -        | -           | -2.0    | 4.0       | -          | -  | A6800+   | -          | -               | -                      | 1.0      |
| 010 | IF | ITVAK | -        | -           | -2.0    | -         | -          | -  | A6800+   | -          | -               | -                      | 1.0      |
| 020 | TF | NUNKI | -        | -           | -2.0    | 3.8       | -          | -  | A6000+   | -          | -               | -                      | 1.0      |
| 030 | TF | SD500 | Y        | -           | -2.0    | 9.2       | -          | -  | -        | -          | -5.4/50         | -                      | 0.3      |
| 040 | FA | SD500 | -        | 292 (294.0) | -2.0    | -         | -          | -  | A4000    | K130-      | -               | -                      | 1.0      |
| 050 | DF | OGDIT | -        | -           | -2.0    | -         | -          | R  | -        | -          | -               | -                      | 1.0      |
| 060 | HM | OGDIT | -        | 348 (350.0) | -2.0    | 1 MIN     | -          | L  | A8000    | -          | -               | -                      | 1.0      |

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.